



材 質：彈簧鋼 SAE 1075
 (有"R"標號，為不銹鋼 AISI302)
 表面處理：藍熱化
 規格有標記 "*" 為兩波浪,其他為三波浪

波浪彈性墊圈

單位:mm

產品編號	外徑 O.D	內徑 I.D	厚度 t	自由高 L ₀	負荷 高度 L ₁	最大負荷 P ₁ (kg)	產品編號	外徑 O.D	內徑 I.D	厚度 t	自由高 L ₀	負荷 高度 L ₁	最大負荷 P ₁ (kg)
W61300R	* 4.65	3.40	0.09	0.58	0.30	0.113-0.227	W61530	39.19	30.51	0.43	2.67	1.32	8.633-10.449
W61310R	* 6.15	4.92	0.14	0.76	0.38	0.227-0.454	W61540	39.19	30.51	0.51	3.18	1.57	12.265-15.888
W61320R	* 7.75	6.17	0.17	0.76	0.38	0.227-0.454	W61550	40.46	31.47	0.46	2.79	1.39	9.541-12.265
W61330	9.32	6.73	0.15	0.76	0.38	0.908-1.816	W61560	41.17	32.03	0.47	2.84	1.42	9.990-12.714
W61340R	9.32	6.73	0.15	0.76	0.38	0.908-1.816	W61570	46.20	35.66	0.51	3.18	1.57	11.806-15.439
W61350	12.29	10.08	0.23	0.74	0.51	1.362-2.270	W61580	51.51	40.01	0.56	3.56	1.75	14.071-17.714
W61360	12.50	8.89	0.18	0.89	0.51	1.362-2.270	W61590	54.15	42.11	0.58	3.76	1.85	14.990-19.531
W61370R	12.50	8.89	0.18	0.89	0.51	1.362-2.270	W61600	61.47	47.55	0.64	4.27	2.08	18.163-22.755
W61380	15.44	11.66	0.20	0.94	0.64	1.362-2.270	W61610	67.18	52.55	0.71	4.67	2.29	22.755-29.082
W61390	15.70	11.18	0.20	1.02	0.64	1.362-2.270	W61620	71.53	55.88	0.76	5.00	2.47	25.918-33.163
W61400R	15.70	11.18	0.20	1.02	0.64	1.362-2.270	W61630	79.20	61.47	0.89	5.26	2.64	35.000-45.000
W61410	18.57	14.94	0.23	1.19	0.76	1.362-2.270	W61640	84.53	66.12	0.91	5.77	2.84	35.918-45.918
W61420	18.64	13.49	0.23	1.27	0.76	1.816-3.184	W61650	89.38	69.60	0.97	5.94	2.95	40.000-50.816
W61430R	18.64	13.49	0.23	1.27	0.76	1.816-3.184	W61660	99.49	77.39	1.07	6.55	3.25	47.653-61.327
W61440	21.72	16.51	0.25	1.52	0.76	1.816-3.184	W61670	109.22	85.60	1.14	7.67	3.76	55.816-71.327
W61450R	21.72	16.51	0.25	1.52	0.76	1.816-3.184	W61680	117.53	91.74	1.19	8.49	4.11	63.571-80.816
W61460	23.50	18.26	0.25	1.68	0.84	2.724-4.092	W61690	126.92	98.81	1.27	9.02	4.37	70.816-89.898
W61470	25.50	19.81	0.27	1.80	0.89	3.184-4.541	W61700	137.36	106.88	1.35	9.86	4.75	78.571-100.306
W61480	27.43	21.31	0.29	1.85	0.91	3.633-5.449	W61710	147.75	115.06	1.40	11.18	5.31	86.735-110.306
W61490	27.99	21.74	0.30	1.91	0.94	4.092-5.908	W61720	156.79	122.00	1.47	11.76	5.59	95.408-121.735
W61500	29.44	22.89	0.33	2.03	1.02	4.541-6.357	W61730	166.37	130.05	1.55	12.60	5.97	103.980-132.143
W61510	31.37	24.41	0.36	2.21	1.09	5.908-7.724	W61740	176.40	137.36	1.60	13.65	6.43	112.653-143.469
W61520	34.32	26.70	0.38	2.51	1.24	7.265-9.082	W61750	186.06	144.07	1.65	14.61	6.83	121.735-155.306